



**Product:** [1337A](#)

Fieldbus, 1 Pr #18 Str TC, PO Ins, IS/OS, 1C #18 Str PVC Ins, PVC Jkt, 600V TC-ER

[Request Sample](#)

## Product Description

Fieldbus, 1 Pair 18AWG (7x26) Tinned Copper, PO Insulation, Individual & Overall Beldfoil® Shield, 1 Conductor 18AWG (7x26) Tinned Copper, PVC Insulation, Orange PVC Outer Jacket, 600V TC-ER

## Technical Specifications

### Product Overview

Suitable Applications:	harsh environment digital and serial two-way communication, oil and gas extraction and refining sites, petrochemical, Profibus process automation or Foundation FieldBus process automation, extreme temperature environments, exposure to humidity/moisture, dust, and oil, remote locations long distance applications, etc.
------------------------	--

### Construction Details

#### Conductor

Element	Size	Stranding	Material
Pair(s)	18 AWG	7x26	TC - Tinned Copper

#### Insulation

Element	Material	Color Code	Notes
Conductor(s)	PP - Polypropylene	Blue & Orange	
Ground	PP - Polypropylene	Green/Yellow	Flame Retardant

#### Inner Shield

Element
Data Pair(s)

#### Outer Shield

Material
Bi-Laminate (Alum+Poly)

#### Outer Jacket

Material	Nom. Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.060 in (1.5 mm)	0.362 in (9.19 mm)

### Electrical Characteristics

#### Electricals

Nom. Conductor DCR	Nom. Characteristic Impedance	Max. Current
7.06 Ohm/1000ft	100 Ohm	5 Amps per Conductor

Nom. Outer Shield DCR:	1.51 Ohm/1000ft (4.95 Ohm/km)
------------------------	-------------------------------

#### Voltage

UL Voltage Rating
600 V

### Mechanical Characteristics

#### Temperature

UL Temperature	Operating
75°C	-30°C to +75°C

#### Bend Radius

Stationary Min.	Installation Min.
3.62 in (91.9 mm)	3.62 in (91.9 mm)

Max. Pull Tension:	44.8 lbs (20.3 kg)
Bulk Cable Weight:	68 lbs/1000ft

#### Standards and Compliance

Environmental Suitability:	Outdoor, Sunlight Resistance, UV Resistance, Oil Resistance
Flammability / Reaction to Fire:	UL1685 UL Loading
NEC / UL Compliance:	Article 725, TC-ER

#### History

Update and Revision:	Revision Number: 0.413 Revision Date: 08-10-2023
----------------------	--

#### Part Numbers

##### Variants

Item #	Color	UPC
1337A 00310000	Orange	612825112266

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.